

AS81659/33

FEDERAL SUPPLY CLASS
5935


NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-81659/33B AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-81659/33B. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: MIL-C-81659

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

CONNECTORS, ELECTRICAL, RECTANGULAR,
PLUG, CRIMP CONTACTS, (DUAL INSERT, TYPE II, CLASS 1
(-65°C TO +125°C), SERIES 2, SHELL DESIGNATOR A)

AS81659/33
SHEET 1 OF 4

ISSUED 2004-05

Copyright 2004 SAE International


All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

FOR CONNECTOR DRAWING SEE PAGE 2.



SUGGESTED PANEL CUT-OUT DIMENSIONS

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.006	.15	.125	3.18	.521	13.23	1.387	35.23	1.985	50.42
.047	1.19	.133	3.38	.541	13.74	1.3915	35.34	2.015	51.18
.060	1.52	.178	4.52	.7185	18.25	1.427	36.25	2.320	58.93
.093	2.36	.198	5.03	.885	22.48	1.437	36.50	2.440	61.98
.115	2.92	.225	5.72	.897	22.78	1.447	36.75	2.450	62.23
.117	2.97	.235	5.97	.927	23.55	1.541	39.14	2.783	70.69
.118	3.00	.281	7.14	.947	24.05	1.720	43.69	3.095	78.61
.122	3.10	.297	7.54	1.367	34.72	1.730	43.94	3.125	79.38

NOTES:

1. DIMENSIONS ARE IN INCHES.
2. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
3. DIMENSIONS APPLY AFTER PLATING.
4. NORMAL (01) POLARIZATION POSITION SHOWN. FOR ALTERNATE POSITIONS SEE MIL-C-81659.
5. FOR LOCATION OF DATUMS G AND H REFER TO MIL-C-81659, FIGURE 6.

REQUIREMENTS:

INSERT ARRANGEMENTS SHALL BE IN ACCORDANCE WITH MS3157.

CONTACTS SHALL BE IN ACCORDANCE WITH MIL-C-39029/11 OR MIL-C-39029/12 AS APPLICABLE.

INSTALLING AND REMOVAL TOOLS SHALL BE IN ACCORDANCE WITH MS3156 OR MS3447.